



## PRODUCT DATA

### Castrol Power RS™ Racing 4T Motorcycle Oil

Castrol Power RS™ Racing 4T with Trizone Technology is a premium quality, full synthetic 4-stroke motorcycle oil designed to ensure maximum power and performance, even under the most demanding riding conditions. Its anti-friction formulation is proven to increase acceleration compared to conventional motorcycle oils.

#### Features and Benefits

- Race derived technology for maximum engine acceleration
- Extreme high temperature air-cooled performance and water-cooled engine performance
- Excellent shear stability to prevent viscosity breakdown
- Superior high speed engine protection to help extend engine life
- Outstanding oil consumption and control, gear shift quality and wet clutch performance

#### Warranty and Protection Requirements

- Exceeds engine manufacturer's warranty requirements for applications requiring API SL and JASO MA-2

#### Typical Properties\*

	Method	5W-40	10W-40	10W-50
API		SL	SL	SL
JASO		MA-2	MA-2	MA-2
Viscosity @ 100C, cSt	ASTM D445	13.0	13.3	17.14
Viscosity @ 210F, SUS	ASTM D2161	70.2	71.3	86.5
Viscosity @ 40C, cSt	ASTM D445	74.96	83.05	110.0
Viscosity Index	ASTM D2270	171	155	166
Low Temp ( C) Cranking Viscosity, cP max.	ASTM D5293	6,600 @ -30	7,000 @ -25	7,000 @ -25
Low Temp ( C) Pumping Viscosity, cP max.	ASTM D4684	60,000 @ -35	60,000 @ -30	60,000 @ -30
HT /HS Viscosity, cP min	ASTM D4683	2.9	2.9	3.7
Pour Point, F (C) max	ASTM D97	0 (-18)	0 (-18)	0 (-18)
Flash Point, PMCC, C min	ASTM D93	>200	>200	>200
Density @ 15C, Relative	ASTM D4052	0.857	0.853	0.850
Pounds per Gallon		7.137	7.102	7.076

\* Due to continual product research and development, the information contained herein is based on products purchased in the U.S. and subject to change without notification. Typical properties may vary slightly.



## Part Numbers and UPCs

### Packaged Goods

SAE Grade	5W-40	10W-40	10W-50
Case Size	6/1 QT	6/1 QT	6/1 QT
Case Part No.	06410	06078	06412
Bottle/ Unit UPC	0-79191-06411-5	0-79191-06079-7	0-79191-06413-9
Case UPC	0-79191-06410-8	0-79191-06078-0	0-79191-06412-2

## Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the applications referred to above and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDSs are available upon request through your sales contact office, or via the Internet at [www.castrol.com/us](http://www.castrol.com/us). This product should not be used for purposes other than the applications referred to above. If disposing of used product, take care to protect the environment, return used oil to collection center.

BP Lubricants USA Inc.  
1500 Valley Road  
Wayne, NJ 07470  
Telephone: 1,800.462.0835  
Email: [contactus@bp.com](mailto:contactus@bp.com)  
©2011 BP Lubricants USA Inc. All rights reserved.

[www.castrol.com/us](http://www.castrol.com/us)